

### PRODUCT

#### COLOR NAMES/SKU:

**Cappadocia** ECO67980XL

**Chocolate Hills** ECO35410XL

**Mali** ECO78340XL

**Acacia** (Discontinued) ECO14290XL

### CONSTRUCTION

6mm Rigid Core (Stone and Virgin DOTP Composite) (Single Extrusion Stone Polymer Composite)

☑ 1.5mm IXPE attached cushion

☑ 5 unique planks per pattern, 10 with a flip

### INSTALLATION

#### Click Unilin Locking Sytem

Please reference our installation instruction for futher details

### SIZE/PACKAGING

**Plank Size:** 9" x 70"

**Planks/Carton:** 8

**Sq.Ft/Carton:** 26.24

**Cartons/Pallet:** 56

**Sq.Ft/Pallet:** 1469.44

**Sq.Ft/Container:** 29,388.8

### WEAR LAYERS

20 Mil

### TEST DATA

ASTM E492-09

#### IMPACT SOUND CONDUCTION

IIC 60 STC 60

ASTM E90-09

#### AIRBONE SOUND CONDUCTION

STC 62 IIC 62 HIIIC 69

ASTM F2199-20

#### DIMENSIONAL STABILITY

Meets or Exceeds

ASTM D1037-12

#### STATIC BENDING

(MPa) 18.9

ASTM F1514-19

#### RESISTANCE TO HEAT AND COLD

Meets or Exceeds, average  $\Delta E^*$  0.22

ASTM C518

#### THERMAL RESISTANCE

R Value 0.05 or 0.135W/(M.K)

ASTM F2199-09

#### DIMENSIONAL STABILITY & CURLING AFTER EXPOSURE TO HEAT

MD 0.040 AMD 0.037

ASTM D4060-19

#### ABRASION RESISTANCE

Weight loss (mg) 33.3 | Wear Index (mg/1000r) 3.3

ASTM D2394

#### SLIP RESISTANCE DCOF SLIDING

Dry: R10 | Wet: R10

ASTM E648

#### CRITICAL RADIANT FLUX

Class 1

ASTM F1515-21

#### RESISTANCE TO LIGTH

$\Delta E \leq 8.0$

ISO1058 & ISO105-B02

#### COLOUR FASTNESS TO LIGTH

6 above

ASTM F925-13

#### RESISTANCE TO CHEMICALS

No change, Not affected



Discover more about  
Ecoshield on our website.  
Scan the QR code to  
access it.  
[ecoshieldfloors.com/](https://ecoshieldfloors.com/)



20mil Wear  
Layer



Sound  
Reducing



Fast&Secure  
clip system



Waterproof

**ecoshield**  
VINYL FLOORING